



AK1.5-TN-PE

DIN Rail Terminal Blocks > Spring Clamp Connection

Date:2026-06-18Version:1.1



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

Product Description

Green-Yellow (default)

General information

Short description	DIN Rail terminal blocks, Grounding terminal blocks
Category	Grounding terminal blocks
Color	Green-Yellow (default)
Connection method	Spring Clamp Connection
Type of locking	Rail Mounting
Length (mm)	60.8
Width (mm)	4.2
Height (mm)	35.5
Level	Single level
Connection points	3

Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	V0

Insulation resistance

 $\geq 500\text{M}\Omega$ at DC 500V

Connection data-IEC

Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm ²)	0.14
Conductor cross section solid.max (mm ²)	1.5
Conductor cross section stranded. min (mm ²)	0.14
Conductor cross section stranded. max (mm ²)	1.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm ²)	0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm ²)	0.75
Conductor cross section flexible, with min ferrule with plastic sleeve (mm ²)	0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm ²)	0.75
Slotted screwdriver size (Blade thickness x Width)(mm)	0.4x2.5
Stripping Length (mm)	10
Mounting rail	TS-35
End cover plate required	YES
Grounding connections	YES

Connection data-UL

Rated voltage (UL/CUL Group B)(V)	600
Min. solid wire connection (AWG) acc. to UL/CUL	30
Max. solid wire connection AWG acc. to UL/CUL	14
Min. stranded wire connection AWG acc. to UL/CUL	30
Max. stranded wire connection AWG acc. to UL/CUL	14

Environment & Safety

Back of the hand protection (YES or NO)	YES
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40

UL Recognized

Wire Range (Group B)(AWG)	30~14
---------------------------	-------

Rated voltage (Group B)(V)	600
Wire Range (Group C)(AWG)	30~14
Rated voltage (Group C)(V)	600



CUL Recognized

Wire Range (Group B)(AWG)	30~14
Rated voltage (Group B)(V)	600
Wire Range (Group C)(AWG)	30~14
Rated voltage (Group C)(V)	600

VDE Approval

Wire Range (mm ²)	0.14~1.5
Rated voltage (V)	630

Drawings



circuit diagram



Approvals







Accessories

MKG-001

Label

	For SS2N, SS6N, SS7N, DP Series, AK Series. Using UL94-V0 class of insulation material.
	MKG-002 Label For SS2N, SS6N, SS7N, DP Series, AK Series. Using UL94-V0 class of insulation material.
	SS6N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	TM41LW Marking Label For BEST APPLICATION : DP1.5N, DP1.5N-PE, DP1.5N-TN, DP1.5N-TN-PE, DP1.5N-TR, DP1.5N-TR-PE, DPH1.5, DPH1.5-PE, DPP1.5N, DPP1.5N-PV, DPP1.5N-L2PE, DPP1.5N-PE, DPH1.5SG AVAILABLE APPLICATION : AK1.5, AK1.5-PE, AK1.5-TN, AK1.5-TN-PE, AK1.5-TR, AK1.5-TR-PE, AKK1.5 White color. Using UL94-V0 class of insulation material.
	SS11 End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	TM46LW Marking Label For BEST APPLICATION : DP1.5N, DP1.5N-PE, DP1.5N-TN, DP1.5N-TN-PE, DP1.5N-TR, DP1.5N-TR-PE, DPH1.5, DPH1.5-PE AVAILABLE APPLICATION : AK1.5, AK1.5-PE, AK1.5-TN, AK1.5-TN-PE, AK1.5-TR, AK1.5-TR-PE White color. Using UL94-V0 class of insulation material.
	TS-35 DIN-Rail For DP / DK..N / DK.. / AK / DKB / DKU.. /DKM.. series. Material is iron. Length of 1000mm / 2000mm.

	TS-35/15 DIN-Rail For DK / DK-PE series. Material is iron. Length of 1000mm / 2000mm.
	TS-35C DIN rail end cap For TS-35 rail. Black color. Using UL94-V2 class of insulation material.
	TM-R100 Continuous Flat Marking Labels
	TM-R200 Continuous Flat Marking Labels
	SS7N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS4N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS13 End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS5N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS2N



End Bracket

For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.