



DP16-PE

DIN Rail Terminal Blocks > Push-in Design

Date:2026-06-18



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

Product Description

600V, Green-Yellow (default)

General information

Short description	Grounding Terminal Block, Push-in Design
Category	Grounding Terminal Block
Color	Green-Yellow (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	76.5
Width (mm)	12
Height (mm)	53.1
Number of positions	≥1P
Level	Single level
Connection points	2

Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	V0

Insulation resistance	$\geq 500\text{M}\Omega$ at DC 500V
-----------------------	-------------------------------------

Connection data-IEC

Rated voltage (V)	1000
Rated voltage (III/3)(V)	1000
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm ²)	0.5
Conductor cross section solid.max (mm ²)	25
Conductor cross section stranded. min (mm ²)	0.5
Conductor cross section stranded. max (mm ²)	16
Conductor cross section flexible, with min ferrule without plastic sleeve (mm ²)	0.5
Conductor cross section flexible, with max ferrule without plastic sleeve (mm ²)	16
Conductor cross section flexible, with min ferrule with plastic sleeve (mm ²)	0.5
Conductor cross section flexible, with max ferrule with plastic sleeve (mm ²)	16
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm ²)	1.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm ²)	4
Slotted screwdriver size (Blade thickness x Width)(mm)	1.0x5.5
Stripping Length (mm)	18
Mounting rail	TS-35、TS-35/15
End cover plate required	YES
Grounding connections	YES

Connection data-UL

Rated voltage (UL/CUL Group B)(V)	600
Rated voltage (UL/CUL Group C)(V)	600
Min. solid wire connection (AWG) acc. to UL/CUL	20
Max. solid wire connection AWG acc. to UL/CUL	4
Min. stranded wire connection AWG acc. to UL/CUL	20
Max. stranded wire connection AWG acc. to UL/CUL	4

Environment & Safety

Back of the hand protection (YES or NO)	YES
---	-----

Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40



UL Recognized

Wire Range (Group B)(AWG)	20~4
Rated voltage (Group B)(V)	600
Wire Range (Group C)(AWG)	20~4
Rated voltage (Group C)(V)	600

CUL Recognized

Wire Range (Group B)(AWG)	20~4
Rated voltage (Group B)(V)	600
Wire Range (Group C)(AWG)	20~4
Rated voltage (Group C)(V)	600

Drawings



Approvals




Accessories



TM50LW

Marking Label

For BEST APPLICATION : DP10, DP10-PE, DP10-TN, DP10-TN-PE, DKD10-P001, DPHD10-P001, DPH10 Series, AK10, AK10-PE, AK10-TN, AK10-TN-PE, DK10N, DK10N-PE, DK10N-TN, SS6N AVAILABLE APPLICATION : DP16, DP16-PE, DP16-TN, DP16-TN-PE, DPH16 Series, AK16, AK16-PE, AK16-TN, AK35, DK10-PE, DK16N, DK16N-PE, DK16H, DK16-PE, DK16T, DK35N, DK35H, DK35H-PE, DK50, DK50-PE, DK95, DK95-PE, DK150, DK240, DKM Series White color. Using UL94-V0 class of insulation material.



SS6N

End Bracket

For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.



TM45LW

Marking Label

For BEST APPLICATION : DP10, DP10-PE, DP10-TN, DP10-TN-PE, DKD10-P001, DPHD10-P001, DPH10 Series, AK10, AK10-PE, AK10-TN, AK10-TN-PE AVAILABLE APPLICATION : DP16, DP16-PE, DP16-TN, DP16-TN-PE, DPH16 Series, AK16, AK16-PE, AK16-TN, AK35, DPD10-P001, DPD16-P001, DK10-TF, DK10-TFA White color. Using UL94-V0 class of insulation material.



DP16C

End Cover

For DP16 Beige color. Using UL94-V0 class of insulation material.



SS11

End Bracket

For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.







TS-35


DIN-Rail

For DP / DK..N / DK.. / AK / DKB / DKU.. /DKM.. series. Material is iron. Length of 1000mm / 2000mm.

TS-35C

DIN rail end cap

	For TS-35 rail. Black color. Using UL94-V2 class of insulation material.
	TM-R100 Continuous Flat Marking Labels
	TM-R200 Continuous Flat Marking Labels
	DSD01-1602N Plug-in bridge For DP16 Series, DPH16 Series, AK16, AK16-TN. Red color. Using UL94-V0 class of insulation material.
	SS7N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS4N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS13 End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS5N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS2N



End Bracket

For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.



AKSPS-001-OR

Partition Plate

For DP1.5N, DP2.5N, DP4N, DP1.5N-PE, DP2.5N-PE, DP4N-PE, DPH1.5, DPH1.5-PE, DPH2.5, DPH2.5-PE, DPH2.5-DP, DPH2.5-DP-PE, AK1.5, AK2.5, AK4 Orange color. Using UL94-V0 class of insulation material.