



DP2.5N-TN-PE

DIN Rail Terminal Blocks > Push-in Design

Date:2026-06-18



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.
The final product is made according to engineering drawing.

Product Description

600V, Green-Yellow (default)

General information

Short description	Grounding Terminal Block, Push-in Design
Category	Grounding Terminal Blocks
Color	Green-Yellow (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	60.8
Width (mm)	5.1
Height (mm)	35
Number of positions	≥1P
Level	Single level
Connection points	3

Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	V0

Insulation resistance	$\geq 500\text{M}\Omega$ at DC 500V
-----------------------	-------------------------------------

Connection data-IEC

Rated voltage (V)	800
Rated voltage (III/3)(V)	800
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm ²)	0.14
Conductor cross section solid.max (mm ²)	4
Conductor cross section stranded. min (mm ²)	0.14
Conductor cross section stranded. max (mm ²)	2.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm ²)	0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm ²)	2.5
Conductor cross section flexible, with min ferrule with plastic sleeve (mm ²)	0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm ²)	2.5
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm ²)	0.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm ²)	0.5
Slotted screwdriver size (Blade thickness x Width)(mm)	0.6x3.5
Stripping Length (mm)	10
Mounting rail	TS-35
End cover plate required	YES
Grounding connections	YES

Connection data-UL


Rated voltage (UL/CUL Group B)(V)	600
Rated voltage (UL/CUL Group C)(V)	600
Min. solid wire connection (AWG) acc. to UL/CUL	26
Max. solid wire connection AWG acc. to UL/CUL	12
Min. stranded wire connection AWG acc. to UL/CUL	26
Max. stranded wire connection AWG acc. to UL/CUL	12

Environment & Safety

Back of the hand protection (YES or NO)	YES
---	-----

Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40

Drawings



Approvals



Accessories



DSD01-2.5XXN




Plug-in bridge

For DP2.5N Series, DPP2.5N Series, DP2.5N-3L Series, DP2.5SG Series, DPES2.5, DPES2.5-PE, DKD10-P001, DPHD10-P001, DPD16-P001, DPD10-P001, DPH2.5 Series, DPPES2.5, DPPES2.5-PE, AK2.5 Series, AKK2.5, AKK2.5-D01, AKK2.5-D02, AKK2.5-D03, AKK2.5-D04, AKK2.5-PV Red color. Using UL94-V0 class of insulation material.








TM42LW

Marking Label

	Series, DK2.5L-3L, DK2.5P AVAILABLE APPLICATION : DPES2.5, DPES2.5-PE, DP2.5PG, DP2.5SG Series, DPPES2.5, DPPES2.5-PE White color. Using UL94-V0 class of insulation material. For BEST APPLICATION : DP2.5N Series, DP2.5N-3L-SPE, DPH2.5 Series, AK2.5 Series, DKES1.5N2, DKES1.5N3, DPP2.5N Series, DP2.5N-3L, DP2.5N-3L-PV, DP2.5N-3L-L3PE, DP2.5N-3L-PE, DPH1.5SGU, DK2.5S, DK1.5SG Series, PM2.5N-XXP, PM2.5WN-XXP, PMM2.5WN-XXP, AKK2.5, AKK2.5-PV, AKK2.5-PE, AKK2.5-D For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	AKSPS-003-OR Partition For DP..N-TN Series, DP..N-TN-PE Series, DPH2.5-DP-TN, DPH2.5-DP-TN-PE, AK..-TN Series, AK2.5T Series, AK4T Series Orange color. Using UL94-V0 class of insulation material.
	TM47LW Marking Label For BEST APPLICATION : DP2.5N Series, DP2.5N-3L-SPE, DPH2.5 Series, AK2.5 Series, DKES1.5N2, DKES1.5N3, DK2.5N Series, DKK2.5N Series, DK2.5N-3L Series AVAILABLE APPLICATION : DKES1.5, DK2.5-PE White color. Using UL94-V0 class of insulation material.
	MKG-003 Label For SS2N, SS6N, SS7N, DP Series, AK Series. Using UL94-V0 class of insulation material.
	SS11 End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	MKG-004 Label For SS2N, SS6N, SS7N, DP Series, AK Series. Using UL94-V0 class of insulation material.
	TS-35

	DIN-Rail For DP / DK..N / DK.. / AK / DKB / DKU.. /DKM.. series. Material is iron. Length of 1000mm / 2000mm.
	0208-E001 Spacer For DPH2.5 Series, DP2.5N Series, DPP2.5N Series, DPD10-P001, DKD10-P001, DPHD10-P001, DPD16-P001, DP2.5SG, DP2.5SG-L24*, DP2.5SGT, DP2.5SGT-L24*, DP2.5SG, DP2.5SG-L24*, DP2.5SGR, DP2.5SGR-L24*, DP2.5SGRT, DP2.5SGRT-L24*, DPES2.5, DPPES2.5, DPES2.5-PE, DPPES2.5-PE, DP2.5N-T, AK2.5 Series Red color. Using UL94-V0 class of insulation material.
	0208-T001 Test Plug For DPH2.5 Series, DP2.5N Series, DPP2.5N Series, DPD10-P001, DKD10-P001, DPHD10-P001, DPD16-P001, DP2.5SG, DP2.5SG-L24*, DP2.5SGT, DP2.5SGT-L24*, DP2.5SG, DP2.5SG-L24*, DP2.5SGR, DP2.5SGR-L24*, DP2.5SGRT, DP2.5SGRT-L24*, DPES2.5, DPPES2.5, DPES2.5-PE, DPPES2.5-PE, DP2.5N-T, AK2.5 Series Red color. Using UL94-V0 class of insulation material.
	TS-35C DIN rail end cap For TS-35 rail. Black color. Using UL94-V2 class of insulation material.
	DP2.5C-TN End Cover For DP2.5N-TN Beige color. Using UL94-V0 class of insulation material.
	TM-R100 Continuous Flat Marking Labels
	TM-R200 Continuous Flat Marking Labels

	SS7N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS4N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS13 End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	DSD03-2.5/6 Plug-in bridge For DP2.5N Series, DP6N Series, DKD35-P001, DKD35-P002, DPD10-P001, DPD16-P001, DKD10-P001, DPHD10-P001 Red color. Using UL94-V0 class of insulation material.
	SS5N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.
	SS2N End Bracket For TS-35, TS-35/15 rails. Beige color. Using UL94-V0 class of insulation material.