

GFNC-1A3A

iO-GRID NEMO Integrated Remote I/O Module


Integrated Remote I/O module with EtherCAT communication, featuring 16 digital inputs and 16 digital outputs.

SINK(NPN) I/O design for flexible machine control applications.

Pluggable terminal block and push-in wiring enable faster installation and easier maintenance.

Integrated point indicators and independent LED status display make I/O status easy to identify.

Dual RJ45 ports support distributed station architecture and flexible machine expansion.



Product
Certification



Technical Specifications

System Voltage Supply	24 VDC (-15%~+20%)
Current Draw	Max. 200mA@24VDC
Input / Output Signal Type	Sink
Input Voltage Range for Signal (0)	15VDC...30 VDC
Input Voltage Range for Signal (1)	0 VDC...10 VDC
Load Specification	Ohmic load/ inductive load / lamp load
Protective Circuit	Overvoltage Protection / Undervoltage Protection / Overcurrent Protection
Max. Output Current In Single Channel	0.5 A
Connection Method	Push-in connection
Isolation Method	Digital Isolator
Indicators	16 Green / Input Status / Output Status; Power Status : Green; System Status : Green; Alarm Status : Green/Red; Communication Status : Green/Red
Number Port	2

Communication Specifications

Protocol	EtherCAT
----------	----------


General Specifications

Dimensions (W*D*H)	25 x 116 x 85 mm
Weight	150 g
Operating Temperature	-10 ... 60 °C
Storage Temperature	-25...+85°C



Permissible Humidity(Non-condensing)	RH 95%
Altitude Limit	< 2000 m
Ingress Protection (IP)	IP 20
Pollution Severity	II
Safety Approval	UL / CE
Wire Range (IEC / UL)	0.2 mm ² ~ 1.5 mm ² / AWG 24~16

Product Drawing



The company reserves the right to modify and change the design of products.