


GFNH-1A1A

iO-GRID NEMO Integrated Remote I/O Module

Integrated Remote I/O module with CC-Link communication and 32 digital input points. SINK(NPN) input design for multi-point signal acquisition applications.

Pluggable terminal block and push-in wiring enable faster installation and easier wiring. Integrated point indicators and independent LED status display make module status easy to identify.

Equipped with daisy-chain communication interfaces for distributed station architecture and flexible machine expansion



Product
Certification



Technical Specifications

System Voltage Supply	24 VDC (-15%~+20%)
Current Draw	Max.80mA@24VDC
Input / Output Signal Type	Sink
Input Voltage Range for Signal (0)	15VDC...30 VDC
Input Voltage Range for Signal (1)	0 VDC...10 VDC
Protective Circuit	Overvoltage Protection / Undervoltage Protection / Overcurrent Protection
Connection Method	Push-in connection
Isolation Method	Photocoupler Isolator
Indicators	32 Green / Input Status; Power Status(PWR) : Green; Alarm Status(LERR) : Red; System Status(LRUN) : Green; Send Data Status(SD) : Green; Receive Data Status(RD) : Green
Number Port	1

Communication Specifications

Protocol	CC-Link
----------	---------


General Specifications

Dimensions (W*D*H)	25 x 116 x 85 mm
Weight	150 g
Operating Temperature	-10 ... 60 °C
Storage Temperature	-25...+85°C
Permissible Humidity(Non-condensing)	RH 95%



Altitude Limit	< 2000 m
Ingress Protection (IP)	IP 20
Pollution Severity	II
Safety Approval	UL / CE
Wire Range (IEC / UL)	0.2 mm ² ~ 1.5 mm ² / AWG 24~16

Product Drawing



The company reserves the right to modify and change the design of products.